NSN 5305-01-361-2636

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-361-2636 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** 1.185 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.405 inches and 0.435 inches **Head Height:** Between 0.480 inches and 0.510 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.032 inches and 0.093 inches **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener **Material Specification:** Mil-s-5059 military specification single material response primary washerqq-w-423 federal specification single material response springqq-a-225/8 federal specification single material response stand-off **Surface Treatment:** Passivate primary washeranodize stand-offpassivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625, ty1, cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Mil-s-5059 spec.

Mil-std (military Standard):

No Fiig: A003b0