

View Online at <https://aerobasegroup.com/nsn/5305-01-361-2636>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.185 inches

**Head Style:**

Knurled no. 1

**Head Diameter:**

Between 0.405 inches and 0.435 inches

**Head Height:**

Between 0.480 inches and 0.510 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.032 inches and 0.093 inches

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Material:**

Steel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener

**Material Specification:**

Mil-s-5059 military specification single material response primary washerqq-w-423 federal specification single material response springqq-a-225/8 federal specification single material response stand-off

**Surface Treatment:**

Passivate primary washeranodize stand-offpassivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625, ty1, cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.