NSN 5305-01-361-3193

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-361-3193 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.110 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Pan **Head Diameter:** 0.219 inches **Head Height:** 0.080 inches **First Diameter From Head:** Between 0.074 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.140 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 or steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-361-3193

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0