NSN 5305-01-361-3839



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-361-3839 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.276 inches and 0.438 inches **Fastener Length:** 0.438 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.292 inches and 0.332 inches **Internal Drive Style:** Cross recess type 1 **End Application:** An/apq-171 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification 1st treatment response **Special Features:** Head modified process by prime per mil-p-23377, type 01, also epoxy per mil-c-22750, class 03g, type 03, color no36231, per federal standard 595 **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization: