## NSN 5305-01-361-7041

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-361-7041 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.282 inches **Fastener Length:** Between 0.438 inches and 0.500 inches **Head Style:** Undercut pan no. 2 **Head Diameter:** 0.250 inches **Head Height:** 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.188 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.040 inches and 0.050 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303cu or steel comp 303ma or steel comp 303 plus x or steel comp 303 **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-361-7041

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.