## NSN 5305-01-361-7058

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-361-7058

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 1.390 inches and 1.437 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.633 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.312 inches
Grip Length:
Between 0.927 inches and 0.947 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
132000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Nickel alloy 718
Material Specification:
Ams5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-361-7058

Close Tolerance Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0