

View Online at <https://aerobasegroup.com/nsn/5305-01-361-7059>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.561 inches and 0.601 inches

Head Style:

Knurled no. 1

Head Diameter:

0.451 inches

Head Height:

0.290 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.094 inches and 0.155 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Material:

Aluminum alloy 6061 headsteel comp 301 secondary washersteel comp 301 primary washersteel comp 302b springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Qq-a-225/8 federal specification single material response headmil-s-5059a military specification single material response secondary washermil-s-5059a military specification single material response primary washerastm a580 assn standard single material response springqq-a-225/8 federal specification single material response stand-offastm a493 assn standard all material responses fastener

Surface Treatment:

Anodize headpassivate secondary washerpassivate primary washerpassivate springanodize stand-offpassivate fastener

Surface Treatment Specification:

Mil-a-8625 type 1 cl 1 military specification single treatment response headqq-p-35 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625 type 1 cl 1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0