## NSN 5305-01-362-0709

No

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-362-0709 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.559 inches and 0.656 inches **Fastener Length:** Between 0.609 inches and 0.656 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.189 inches **First Diameter From Head:** 0.380 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

## NSN 5305-01-362-0709

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.