

View Online at <https://aerobasegroup.com/nsn/5305-01-362-0938>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.350 inches and 0.440 inches

Fastener Length:

Between 8.250 inches and 8.280 inches

Head Style:

Fillister

Head Diameter:

0.375 inches

Head Height:

0.150 inches

Internal Drive Style:

Slot

End Application:

B52g/h

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

12500 pounds per square inch

Criticality Code Justification:

Feat

Screw Material:

Steel comp 4130 or steel comp 8630

Screw Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response

Screw Surface Treatment Specification:

Qq-p-416, ty1cl2 federal specification 1st treatment response or astmb633, ty2clfe/zn12 assn standard 2nd treatment response

Special Features:

0.070 dia. Drilled hole 8.125 in from head; form, fit and function critical

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.