

View Online at <https://aerobasegroup.com/nsn/5305-01-362-2151>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.146 inches and 1.208 inches

Fastener Length:

1.208 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.359 inches and 0.385 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 99.0 radians and 101.0 radians

Screw Material:

Steel comp 301 and steel comp 302 and steel comp 302b and steel comp 303 and steel comp 303se and steel comp 304 and steel comp 304l and steel comp 305 and steel comp 308 and steel comp 309 and steel comp 309s and steel comp 310 and steel comp 310s and steel comp 314 and steel comp 316 and steel comp 316l and steel comp 317 and steel comp 321 and steel comp 347 and steel comp 348 and steel comp 384 and steel comp 385

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.