NSN 5305-01-362-6169

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-362-6169 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.220 inches and 0.312 inches **Fastener Length:** Between 0.282 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Locking Feature:** Strip locking feature **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Plastic polyamide locking featureiron alloy 660 fastener **Material Specification:** Ams 5731 assn standard single material response fastener or ams 5737 assn standard single material response fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc **Specification Data:**

Shelf Life: N/a

Unit Of Measure:

80205-nas1352 professional/industrial association standard

NSN 5305-01-362-6169

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0