NSN 5305-01-362-6829

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-362-6829 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.310 inches **Fastener Length:** 0.470 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.500 inches **Head Height:** 0.210 inches **First Diameter From Head:** 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.160 inches **Point Style:** Oval **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 1022 **Material Specification:** Astm a108-79 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-f-14072 -262 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-362-6829

Externally Relieved Body Screw - Page 2 of 2



_		 • •				
n	em	it o	riz	2 †1	n	٠.

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.