## NSN 5305-01-362-6838

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-362-6838

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.501 inches
Fastener Length:
Between 0.798 inches and 0.828 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.6335 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.3125 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-362-6838

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

