NSN 5305-01-362-7293

Machine Screw - Page 1 of 2

Thread Class:

Right-hand **Thread Length:**0.782 inches

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5305-01-362-7293

| rastener Lengtn: |
|--|
| Between 0.844 inches and 0.875 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.122 inches and 0.133 inches |
| Locking Feature: |
| Patch or pellet or strip |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Screw Material: |
| Iron alloy 660 |
| Locking Feature Material: |
| Plastic polyamide |
| Screw Material Specification: |
| Ams5737 assn standard single material response |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Shank Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1190 professional/industrial association standard |
| |
| |

NSN 5305-01-362-7293

Machine Screw - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0