NSN 5305-01-362-9848

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-362-9848



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.797 inches and 0.906 inches

Fastener Length:

Between 0.859 inches and 0.906 inches

Head Style:

Dished hexagon

Head Height:

Between 0.080 inches and 0.093 inches

Width Between Flats:

Between 0.243 inches and 0.251 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

16000 pounds per square inch

Screw Material:

Steel comp 4340

Screw Material Specification:

Mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

NSN 5305-01-362-9848

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-5000 spec.

