NSN 5305-01-363-7248



Panel Screw Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-363-7248 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.150 inches **Fastener Length:** Between 0.375 inches and 0.405 inches **Head Style:** Pan **Head Diameter:** 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Material Accommodated Thickness:** Between 0.055 inches and 0.065 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 **Special Features:** Screw head is shouldered; shank is undercut, 0.098 in. Max. Dia. Material: Steel comp 302 springsteel comp 304 stand-offiron alloy 660 fastener **Material Specification:** Qq-w-423 cond b federal specification single material response springqq-s-763 federal specification single material response stand-offams 5731 assn standard single material response fastener or ams 5732 assn standard single material response fastener **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization: