## NSN 5305-01-364-2176

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-364-2176 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.140 inches and 0.160 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Pan **Head Diameter:** 0.219 inches **Head Height:** 0.008 inches **First Diameter From Head:** Between 0.074 inches and 0.080 inches **Second Diameter From Head:** 0.112 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.195 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 688 pounds per square inch **Externally Relieved Body Diameter Quantity:** 2 Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Nas4003 assn standard all treatment responses **Thread Series Designator:** Unjc

Shelf Life:

N/a

## NSN 5305-01-364-2176

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0