NSN 5305-01-365-0868

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-365-0868

Stread Class: 3a Inread Direction: Right-hand Thread Length: Class (Class) Fastene Length: Between 0.280 inches and 0.315 inches Head Style: Pan Between 0.280 inches and 0.219 inches Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.205 inches and 0.219 inches Head Height: Between 0.2070 inches and 0.219 inches Head Height: Torque-set ribbed Thread Diameter: 0.112 inches Thread Olyper Inch (tpi): 40 Min. Tonsile Strength (psi): 10000 pounds per square inch Screw Material Boro Job Strength (psi): 112 inches Pareid Strengt (psi): 1000 pounds per square inch Screw Material Screw Surface Treatment: Ion alloy 680 Gerew Material Specification: Qap-35 federal specification single treatment response Screw Surface Treatment Specification Qap-35 federal specificati	View Online at https://aerobasegroup.com/nsn/5305-01-365-0868
Tread Direction: Right-hand Tread Length: 0.232 inches Fastener Length: Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Neght: Between 0.070 inches and 0.080 inches Heran Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Strength (psi): 113 inches Strew Material: 100000 pounds per square inch Screw Material: Ion alloy 660 Screw Surface Treatment: Passivate Screw Surface Treatment: Qap-35 flederal specification: Qap-35 flederal specification single treatment response Thread Series Designator: Unjc Specification Data: Na Varie Material: Na Marie Between Selfication single treatment response Thread Selfication pata: Na Mator Heasseneii<	Thread Class:
Right-hand Thread Length: 0.232 inches Fastener Length: Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Nimmeter: Between 0.070 inches and 0.219 inches Head Diameter: Detween 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Vaty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material Specification: Name Strate Treatment: Passivate Screw Surface Treatment Specification: Passivate Screw Surface Treatment Specification Paysivate Screw Surface Treatment Specification Qiap-35 federal specification single treatment response Thread Series Designator: Unic Specification Data: Supeification Data: Supeifi	3a
Parenal Length: 0.232 inches Fastener Length: Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Diameter: Between 0.070 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Y Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Passivate Parenal Series Designator: Urijc Screw Surface Treatment Specification: Quep-35 ficterian single treatment response Thread Series Designator: Urijc Surgetification Data: 80205-nas1218 professional/industrial association standard Sheff Life: N/a Lift of Measure: Lift of Measure:	Thread Direction:
0.232 inclust Fastener Length: Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Screw Auterial: 10000 pounds per square inch Screw Material: 1000 pounds per square inch Screw Material Specification: Auss 5741 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Quep-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: Na Li	Right-hand
Fastener Length: Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thready Gty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 573t assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment Specification: Passivate Screw Surface Treatment Specification: Qup-35 federal specification single treatment response Thread Sele Seignato: Junic Surfication Data: B2025-nas1218 professional/industrial association standard Serefication Stale Interd Strength (psi) Hot Of Measure: Iva Surfication Data: B2025-nas1218 professional/industrial association standard <td>Thread Length:</td>	Thread Length:
Between 0.280 inches and 0.315 inches Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Intread Diameter: Ontrol Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Y per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Surface Treatment Passivate Carew Surface Treatment Specification: Arap-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: B0205-nas1218 professional/industrial association standard Shelf Life: N/a Lint Of Measure: - Intertaction:	0.232 inches
Head Style: Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron aloy 660 Screw Muterial Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Chread Series Designator: Unjc Screw Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: - Demilitarization:	Fastener Length:
Pan Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread y ty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Surface Treatment: Passivate Garpe-35 federal specification: Agaptification single treatment response Thread Series Designator: Ling: Byzelfication Data: Byzelfication Data: Byzelfication Data: Na Shelf Life: N/a Lini Of Measure: Image: Image: Partification: Shelf Life: N/a Dimitiarization:	Between 0.280 inches and 0.315 inches
Head Diameter: Between 0.205 inches and 0.219 inches Head Height: Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread y ty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iorn alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Quep-35 federal specification single treatment response Thread Series Designator: Unic Surface Treatment Specification standard Bozofication Data: Bozofication Data: Na Lini Cf Measure: Iva Panel Ivit Of Measure: Iva Bozofication: Iva Demilitarization:	Head Style:
Between 0.205 inches and 0.219 inches Head Height: Between 0.707 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thready Cty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: 10000 pounds per square inch Screw Material Specification: Arms 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Arms Streat Specification single treatment response Thread Series Designator: Unic Specification Data: 8205-nas1218 professional/industrial association standard Sheff Life: N/a Unit Of Measure:	Pan
Head Height:Between 0.070 inches and 0.080 inchesInternal Drive Style:Torque-set ribbedThread Diameter:0.112 inchesThready Qty Per Inch (tpi):40Min. Tonsile Strength (psi):10000 pounds per square inchScrew Material:Ion aloy 660Screw Material Specification:Arres Straftace Treatment:PassivateGrew Surface Treatment Specification:Qu-p-35 federal specification single treatment responseThread Series Designator:UnigSurger Straftace Treatment Specification standardHeightMaterial Specification single treatment responseThread Series Designator:UnigSurger Straftace Treatment Specification standardHeightMainIntred Series Designator:IngicSurger Straftace Treatment Specification standardStreft Life:NaIntif Measure:Intif Measure: <td>Head Diameter:</td>	Head Diameter:
Between 0.070 inches and 0.080 inches Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min.Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw MaterialSpecification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Carp-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: Ro205-nas1218 professional/industrial association standard Screw Internation Data Inte	Between 0.205 inches and 0.219 inches
Internal Drive Style: Torque-set ribbed Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: 170n alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Head Height:
Torque-set ribbed Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Into f Measure: Image: Image: Image:	Between 0.070 inches and 0.080 inches
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Grew Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unic Specification Data: R0205-nas1218 professional/industrial association standard Shelf Life: N/a Intof Measure: - Teremeter Image: Material Seconse Secons	Internal Drive Style:
 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qrq-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N'a Inf Of Measure: - Emiltarization: 	Torque-set ribbed
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Arns 5731 assn standard single material response or arns 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	Thread Diameter:
40 Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	0.112 inches
Min. Tensile Strength (psi): 160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: - Demilitarization:	Thready Qty Per Inch (tpi):
160000 pounds per square inch Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	40
Screw Material: Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	Min. Tensile Strength (psi):
Iron alloy 660 Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	160000 pounds per square inch
Screw Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: - Demilitarization:	Screw Material:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	Iron alloy 660
Screw Surface Treatment: Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	Screw Material Specification:
Passivate Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Life: Dmiltarization:	Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unic Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: 	Screw Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Passivate
Thread Series Designator: Unjc Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Screw Surface Treatment Specification:
Unic Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-p-35 federal specification single treatment response
Specification Data: 80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Series Designator:
80205-nas1218 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization:	Unjc
Shelf Life: N/a Unit Of Measure: Demilitarization:	Specification Data:
N/a Unit Of Measure: Demilitarization:	80205-nas1218 professional/industrial association standard
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
Demilitarization:	Unit Of Measure:
	Demilitarization:
NO	No
Fiig:	Fiig:
A500d0	A500d0