NSN 5305-01-365-1197

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-365-1197

Thread Direction: Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Dimeter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.193 inches and 0.1115 inches Hermal Drive Style: Cross recess type 1 Thread Diameter: O.112 inches Grip Length: Between 0.193 inches and 0.01115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Oty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Q-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data: 80205-nas7500 professional/industrial association standard	Thread Direction: Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.295 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Countersink Angle: Between 0.052 inches and 0.072 inches Thread Diameter: 0.112 inches Grip Length: Countersink Angle: Between 0.052 inches and 0.072 inches Thread Series Designator: Unif Specification Data:	
Thread Direction: Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 180000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatmentes Cadmium and chromate Thread Series Designator: Unif Specification Data:	Thread Direction: Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Oya Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty_2, ct2 federal specification single treatment response Thread Spries Designator: Unjf Specification Data:	Thread Class:
Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpl): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment Specification: Qq-p-416, Vg., cl2 tederal specification single treatment response Thread Series Designator: Unjf Specification Data:	Right-hand Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Filat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thread Diameter: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arns-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, Vg. cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	3a
Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unjf Specification Data:	Thread Length: 0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arns-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unjf Specification Data:	Thread Direction:
0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	0.238 inches Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or arms-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Right-hand
Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Fastener Length: Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 9.0.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arns-5731 assn standard single material response or arns-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Thread Length:
Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Between 0.285 inches and 0.315 inches Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	0.238 inches
Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Otty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unif Specification Data:	Head Style: Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Fastener Length:
Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Flat countersunk Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or arms-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 0.285 inches and 0.315 inches
Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Oty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Head Diameter: Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Head Style:
Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 0.193 inches and 0.226 inches Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Flat countersunk
Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification single treatment response Thread Series Designator: Unjf Specification Data:	Locking Feature: Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arns-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Head Diameter:
Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or arms-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Patch threads or pellet threads or strip threads Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Between 0.193 inches and 0.226 inches
Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Grip Diameter: Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Arms-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Locking Feature:
Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 0.1105 inches and 0.1115 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Patch threads or pellet threads or strip threads
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Grip Diameter:
Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Cross recess type 1 Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 0.1105 inches and 0.1115 inches
Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Thread Diameter: 0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Internal Drive Style:
0.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	O.112 inches Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Cross recess type 1
Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Grip Length: Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Thread Diameter:
Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unif Specification Data:	Between 0.052 inches and 0.072 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	0.112 inches
Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Grip Length:
Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 0.052 inches and 0.072 inches
Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Min. Tensile Strength (psi): 160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Thready Qty Per Inch (tpi):
160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	160000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	40
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Min. Tensile Strength (psi):
Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	160000 pounds per square inch
Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Material: Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Countersink Angle:
Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Iron alloy 660 Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Between 99.0 degrees and 101.0 degrees
Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Material Specification: Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Material:
Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Ams-5731 assn standard single material response or ams-5737 assn standard single material response Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Iron alloy 660
Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Material Specification:
Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Cadmium and chromate Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Ams-5731 assn standard single material response or ams-5737 assn standard single material response
Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Surface Treatment Specification: Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Surface Treatment:
Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Qq-p-416, ty2, cl2 federal specification single treatment response Thread Series Designator: Unjf Specification Data:	Cadmium and chromate
Thread Series Designator: Unjf Specification Data:	Thread Series Designator: Unjf Specification Data:	Surface Treatment Specification:
Unjf Specification Data:	Unjf Specification Data:	Qq-p-416, ty2, cl2 federal specification single treatment response
Specification Data:	Specification Data:	Thread Series Designator:
		Unjf
80205-nas7500 professional/industrial association standard	80205-nas7500 professional/industrial association standard	Specification Data:
		80205-nas7500 professional/industrial association standard
Chalf Life.	Shelf Life:	Shelf Life:

N/a

NSN 5305-01-365-1197

Close Tolerance Screw - Page 2 of 2



	• •						
ın	1+	Of	ΝЛ	ດລ	CI.	ırı	ο.

--

Demilitarization:

No

Fiig:

A003b0