

View Online at <https://aerobasegroup.com/nsn/5305-01-365-1201>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.067 inches and 1.107 inches

Head Style:

Knurled no. 5

Head Diameter:

0.451 inches

Head Height:

0.520 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.031 inches and 0.062 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Product Name:

Navy special project

Lead Thread Quantity:

One

Material:

Aluminum alloy 6061 headsteel comp 302 springaluminum alloy 6061 stand-offsteel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 384 fastener or steel comp 385 fastener or steel comp 410 fastener or steel comp 429 fastener or steel comp 430 fastener or steel comp 431 fastener or steel comp 440c fastener

Material Specification:

Qq-a-225/8 federal specification single material response headqq-w-423 cond b federal specification single material response springqq-a-225/8 federal specification single material response stand-offastm a493 assn standard all material responses fastener or ams5636 assn standard all material responses fastener

Surface Treatment:

Anodize headpassivate springanodize stand-offpassivate fastener

Surface Treatment Specification:

Mil-a-8626 ty1 cl1 military specification single treatment response headqq-p-35 federal specification single treatment response springmil-a-8625 ty1 cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Mil-std (military Standard):

Mil-a-8626 spec.