

View Online at <https://aerobasegroup.com/nsn/5305-01-365-3163>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.512 inches and 0.625 inches

Fastener Length:

Between 0.595 inches and 0.625 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.457 inches and 0.469 inches

Head Height:

Between 0.306 inches and 0.312 inches

Hole Diameter:

Between 0.044 inches and 0.050 inches

Locking Feature:

Pellet locking feature

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.250 inches and 0.253 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 45.0 rockwell c

Hole Configuration Style:

Round internal hexagon

Material:

Plastic polyamide locking feature steel comp 302 fastener or steel comp 303 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, ty2, cl2 federal specification single treatment response fastener

Thread Series Designator:

Unf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0