

View Online at <https://aerobasegroup.com/nsn/5305-01-365-3164>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.512 inches and 0.625 inches

**Fastener Length:**

Between 0.595 inches and 0.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.457 inches and 0.469 inches

**Head Height:**

Between 0.306 inches and 0.313 inches

**Hole Diameter:**

Between 0.044 inches and 0.050 inches

**Locking Feature:**

Patch locking feature

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.312 inches

**Width Across Flats:**

Between 0.250 inches and 0.253 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hole Configuration Style:**

Round internal hexagon

**Product Name:**

Navy special project

**Material:**

Plastic polyamide locking featuresteel fastener

**Surface Treatment:**

Cadmium fastener and chromate fastener

**Surface Treatment Specification:**

Qq-p-416, cl2, ty2 federal specification single treatment response fastener

**Thread Series Designator:**

Unrf

**Specification Data:**

80205-nas1351 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0