NSN 5305-01-365-3164

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-365-3164



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.512 inches and 0.625 inches Fastener Length: Between 0.595 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.457 inches and 0.469 inches **Head Height:** Between 0.306 inches and 0.313 inches Hole Diameter: Between 0.044 inches and 0.050 inches Locking Feature: Patch locking feature **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.250 inches and 0.253 inches **Hole Quantity:** 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hole Configuration Style: Round internal hexagon **Product Name:** Navy special project Material: Plastic polyamide locking featuresteel fastener Surface Treatment: Cadmium fastener and chromate fastener **Surface Treatment Specification:**

Qq-p-416, cl2, ty2 federal specification single treatment response fastener

NSN 5305-01-365-3164

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0