

View Online at <https://aerobasegroup.com/nsn/5305-01-365-3171>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.323 inches

Fastener Length:

Between 0.433 inches and 0.463 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.193 inches and 0.226 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Grip Diameter:

Between 0.1630 inches and 0.1635 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.164 inches

Grip Length:

Between 0.438 inches and 0.458 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Navy special project

Material:

Plastic polyamide locking featureiron alloy 660 fastener

Material Specification:

Bams 5731 assn standard single material response fastener or cams 5737 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjc

Specification Data:

80205-nas7502 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0