NSN 5305-01-365-3861

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-365-3861

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.588 inches
Fastener Length:
Between 0.745 inches and 0.765 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.461 inches and 0.507 inches
Locking Feature:
Patch
Internal Drive Style:
High-torque
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Hardness Rating:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf Shelf Life:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf Shelf Life: N/a
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf Shelf Life: N/a
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure:
160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c Countersink Angle: Between 99.0 degrees and 101.0 radians Screw Material: Steel Screw Surface Treatment: Cadmium and chromate Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: