

View Online at <https://aerobasegroup.com/nsn/5305-01-365-4869>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.363 inches

Fastener Length:

Between 1.910 inches and 1.940 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.360 inches and 0.375 inches

Head Height:

Between 0.115 inches and 0.125 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 1.552 inches and 1.572 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Passivate or chromate and chromate

Surface Treatment Specification:

Qq-p-35 federal specification 1st treatment response or qq-p-416, cl 2, type 2 federal specification 2nd treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1578 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.