NSN 5305-01-366-1114

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-366-1114 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.270 inches and 0.290 inches **Fastener Length:** 0.813 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.367 inches and 0.376 inches **First Diameter From Head:** Between 0.195 inches and 0.205 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.523 inches and 0.543 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response and ams 5737 assn standard single material response **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-366-1114

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0