NSN 5305-01-366-1116

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-366-1116 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.110 inches **Fastener Length:** Between 0.181 inches and 0.185 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.080 inches and 0.084 inches **Head Height:** Between 0.048 inches and 0.050 inches **First Diameter From Head:** Between 0.044 inches and 0.049 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.020 inches and 0.030 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Copper alloy 360 **Material Specification:** Qq-b-626 alloy 360 federal specification single material response **Surface Treatment:** Tin **Surface Treatment Specification:** Mil-t-10727 type 1 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-366-1116

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-t-10727 spec.