NSN 5305-01-366-1140

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-366-1140

| Thread Class: 3a |
|--|
| Ja |
| Thread Direction: |
| |
| Right-hand |
| Thread Length: |
| 0.122 inches |
| Fastener Length: |
| Between 0.172 inches and 0.204 inches |
| Head Style: |
| Button |
| Head Diameter: |
| 0.213 inches |
| Head Height: |
| 0.059 inches |
| Locking Feature: |
| Strip threads |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.112 inches |
| Width Across Flats: |
| 0.062 inches |
| Thready Qty Per Inch (tpi): |
| 40 |
| Min. Tensile Strength (psi): |
| 150000 pounds per square inch |
| Hardness Rating: |
| 38.0 rockwell c and 45.0 rockwell c |
| Material: |
| Steel comp 410 |
| Material Specification: |
| Qqs763 federal specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq+416, ty2cl3 federal specification single treatment response |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-366-1140

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

