NSN 5305-01-366-1141

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-366-1141

View Online at https://aerobasegroup.com/nsn/5305-01-366-1141
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.150 inches and 1.250 inches
Fastener Length:
1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.921 inches and 0.937 inches
Head Height:
Between 0.616 inches and 0.625 inches
Locking Feature:
Pellet threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
33.0 rockwell c and 42.0 rockwell c
Material:
Plastic polyamide locking featuresteel comp 303 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastene
or steel comp 384 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416, cl 2, type 2 federal specification single treatment response fastener
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-366-1141

Socket Head Cap Screw - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0