

View Online at <https://aerobasegroup.com/nsn/5305-01-366-2784>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.098 inches and 0.160 inches

**Fastener Length:**

Between 0.385 inches and 0.425 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.317 inches

**Internal Drive Style:**

Cross recess type 1

**Material Accommodated Thickness:**

Between 0.109 inches and 0.115 inches

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

34.0 rockwell c fastener and 38.0 rockwell c fastener

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 301 primary washer or steel comp 302 primary washer or steel comp 304 primary washer or steel comp 316 primary washer or copper alloy 360 stand-off steel comp 4037 fastener

**Material Specification:**

Mil-s-5059 military specification single material response primary washer qq-b-626, comp 22 federal specification single material response stand-off mil-s-8695 military specification single material response fastener

**Surface Treatment:**

Passivate primary washer cadmium stand-off cadmium fastener

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response primary washer qq-p-416, type 1, class 2 federal specification single treatment response stand-off qq-p-416, type 1, class 2 federal specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5059 spec.