

View Online at <https://aerobasegroup.com/nsn/5305-01-366-2784>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.098 inches and 0.160 inches

Fastener Length:

Between 0.385 inches and 0.425 inches

Head Style:

Flat countersunk

Head Diameter:

0.317 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.109 inches and 0.115 inches

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

34.0 rockwell c fastener and 38.0 rockwell c fastener

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 301 primary washer or steel comp 302 primary washer or steel comp 304 primary washer or steel comp 316 primary washer
copper alloy 360 stand-off steel comp 4037 fastener

Material Specification:

Mil-s-5059 military specification single material response primary washer qq-b-626, comp 22 federal specification single material response
stand-off mil-s-8695 military specification single material response fastener

Surface Treatment:

Passivate primary washer cadmium stand-off cadmium fastener

Surface Treatment Specification:

Mil-std-171 military standard single treatment response primary washer qq-p-416, type 1, class 2 federal specification single treatment
response stand-off qq-p-416, type 1, class 2 federal specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.