

View Online at <https://aerobasegroup.com/nsn/5305-01-366-5698>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.335 inches and 0.390 inches

**Fastener Length:**

Between 0.385 inches and 0.390 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.049 inches and 0.060 inches

**Width Between Flats:**

Between 0.181 inches and 0.187 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.112 inches

**Thready Qty Per Inch (tpi):**

40

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Screw Material:**

Steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 420f or steel comp 420fse or steel comp 430f or steel comp 430fse or steel comp 440f or steel comp 440fse

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 10 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0