NSN 5305-01-366-5698

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-366-5698 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.335 inches and 0.390 inches **Fastener Length:** Between 0.385 inches and 0.390 inches **Head Style:** Hexagon **Head Height:** Between 0.049 inches and 0.060 inches Width Between Flats: Between 0.181 inches and 0.187 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se or steel comp 416 or steel comp 416 plus x or steel comp 416se or steel comp 420f or steel comp 420fse or steel comp 430fse or steel comp 440fse or steel comp 440fse **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 10 style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No **Fiig:**

A500d0