Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-367-2278



**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 1.340 inches and 1.500 inches Fastener Length: Between 1.440 inches and 1.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.735 inches and 0.750 inches **Head Height:** Between 0.492 inches and 0.500 inches Hole Diameter: Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.379 inches Hole Quantity: 6 Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 150000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Steel Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** 

Qq-p-416, type 2 cl 2 federal specification single treatment response

## NSN 5305-01-367-2278

Socket Head Cap Screw - Page 2 of 2



**Thread Series Designator:** 

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0