NSN 5305-01-367-9811

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-367-9811 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.480 inches and 0.520 inches **Fastener Length:** Between 0.980 inches and 1.020 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.355 inches and 0.395 inches **Head Height:** Between 0.420 inches and 0.460 inches Point Length: Between 0.151 inches and 0.161 inches **Point Diameter:** Between 0.125 inches and 0.135 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.344 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 85.0 degrees and 95.0 degrees Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35, type 2 federal specification single treatment response

NSN 5305-01-367-9811

Externally Relieved Body Screw - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0