Externally Relieved Body Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-367-9811



| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.480 inches and 0.520 inches |
| Fastener Length: |
| Between 0.980 inches and 1.020 inches |
| Head Style: |
| Knurled no. 4 |
| Head Diameter: |
| Between 0.355 inches and 0.395 inches |
| Head Height: |
| Between 0.420 inches and 0.460 inches |
| Point Length: |
| Between 0.151 inches and 0.161 inches |
| Point Diameter: |
| Between 0.125 inches and 0.135 inches |
| First Diameter From Head: |
| Between 0.125 inches and 0.135 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.344 inches |
| Point Style: |
| Cone |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Point Chamfer Angle: |
| Between 85.0 degrees and 95.0 degrees |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a581 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Og p. 25. type 2 federal aposition single treatment response |

Qq-p-35, type 2 federal specification single treatment response

Externally Relieved Body Screw - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0