## NSN 5305-01-368-7313

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-368-7313 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.122 inches **Fastener Length:** 0.375 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.191 inches and 0.225 inches First Diameter From Head: Between 0.073 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.141 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 Color: Black bearing surface of head Material: Stainless steel **Material Specification:** Fed standard 66 federal standard all material responses **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-368-7313

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0