## NSN 5305-01-368-8779

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-368-8779

Thread Class:
3a 
Thread Direction:
Right-hand
Thread Length:
0.774 inches
Fastener Length:
Between 1.485 inches and 1.505 inches
Head Style:
Flat countersunk
Head Diameter:
0.490 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
0.218 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp 8740 or steel comp 4140
Material Specification:
Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2, cl2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No
Fiig:
A003b0

## NSN 5305-01-368-8779

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.