NSN 5305-01-369-0870



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-369-0870 **Thread Direction:** Right-hand Thread Length: Between 25.0 millimeters and 30.0 millimeters **Fastener Length:** Between 4.5 millimeters and 5.0 millimeters **Head Style:** Pan **Head Diameter:** Between 3.94 millimeters and 4.24 millimeters **Head Height:** Between 1.40 millimeters and 1.60 millimeters **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 2.2 millimeters Min. Tensile Strength (psi): 80000 pounds per square inch **Thread Pitch In Millimeters:** 0.45 **External Thread Tolerance Class:** 6g **Screw Material:** Steel comp 303 or steel comp 303pb or steel comp 303 plus x or steel comp 303se or steel comp 303ma **Locking Feature Material:** Plastic polyamide **Locking Feature Material Specification:** L-p-410 federal specification single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Μ Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A500d0