

View Online at <https://aerobasegroup.com/nsn/5305-01-369-0871>

Thread Direction:

Right-hand

Thread Length:

Between 25.0 millimeters and 30.5 millimeters

Fastener Length:

Between 7.5 millimeters and 8.0 millimeters

Head Style:

Flat countersunk

Head Diameter:

Between 5.80 millimeters and 6.60 millimeters

Locking Feature:

Patch

Internal Drive Style:

Cross recess type 1

Thread Diameter:

3.0 millimeters

Min. Tensile Strength (psi):

80000 pounds per square inch

Thread Pitch In Millimeters:

0.5

External Thread Tolerance Class:

6g

Countersink Angle:

Between 90.0 degrees and 92.0 degrees

Screw Material:

Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se

Locking Feature Material:

Plastic polyamide

Locking Feature Material Specification:

L-p-410 federal specification single material response

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.