

View Online at <https://aerobasegroup.com/nsn/5305-01-369-0871>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 25.0 millimeters and 30.5 millimeters

**Fastener Length:**

Between 7.5 millimeters and 8.0 millimeters

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 5.80 millimeters and 6.60 millimeters

**Locking Feature:**

Patch

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

3.0 millimeters

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Thread Pitch In Millimeters:**

0.5

**External Thread Tolerance Class:**

6g

**Countersink Angle:**

Between 90.0 degrees and 92.0 degrees

**Screw Material:**

Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se

**Locking Feature Material:**

Plastic polyamide

**Locking Feature Material Specification:**

L-p-410 federal specification single material response

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-c-13924 military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-c-13924 spec.