NSN 5305-01-369-1397

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-1397 **Thread Direction:** Right-hand Thread Length: 8.0 millimeters Fastener Length: Between 7.5 millimeters and 8.0 millimeters **Head Style:** Pan **Head Diameter:** Between 5.50 millimeters and 5.80 millimeters **Head Height:** Between 2.05 millimeters and 2.30 millimeters **Locking Feature:** Patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 3.0 millimeters Min. Tensile Strength (psi): 80000 pounds per square inch **Thread Pitch In Millimeters:** 0.5 **External Thread Tolerance Class:** 6g **Screw Material:** Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se **Locking Feature Material:** Plastic polyamide **Locking Feature Material Specification:** L-p-410 federal specification single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** М Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-369-1397

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.