## NSN 5305-01-369-3262

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-3262 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.440 inches and 0.460 inches **Fastener Length:** Between 0.920 inches and 0.940 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.145 inches and 0.155 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.470 inches and 0.490 inches **Point Style:** Flat **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** Qq-s-763 federal specification all material responses or fed-std-66 federal standard all material responses **Surface Treatment:** Oxide **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-369-3262

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0