Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-369-3262

Thread Class	
3a	
Thread Direc	tion:
Right-hand	
Thread Leng	th:
Between 0.44	0 inches and 0.460 inches
Fastener Len	gth:
Between 0.92	0 inches and 0.940 inches
Head Style:	
Pan	
Head Diamet	er:
Between 0.35	7 inches and 0.373 inches
Head Height:	
Between 0.12	2 inches and 0.133 inches
First Diamete	er From Head:
Between 0.14	5 inches and 0.155 inches
Distance Fro	m Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.47	0 inches and 0.490 inches
Point Style:	
Flat	
Internal Drive	e Style:
Cross recess	type ii
Thread Diam	eter:
0.190 inches	
Thready Qty	Per Inch (tpi):
32	
Externally Re	elieved Body Diameter Quantity:
1	
Material:	
Steel comp 30	02 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Material Spee	cification:
Qq-s-763 fede	eral specification all material responses or fed-std-66 federal standard all material responses
Surface Trea	tment:
Oxide	
Thread Serie	s Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizati	ion:
No	

NSN 5305-01-369-3262

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

