NSN 5305-01-369-3506

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-3506

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
0.276 inches	
Fastener Length:	
Between 0.511 inches a	nd 0.541 inches
Head Style:	
Pan	
Head Diameter:	
Between 0.256 inches a	nd 0.270 inches
Head Height:	
Between 0.087 inches a	nd 0.097 inches
Grip Diameter:	
Between 0.1365 inches	and 0.1375 inches
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.138 inches	
Grip Length:	
Between 0.240 inches a	nd 0.260 inches
Thready Qty Per Inch (pi):
32	
Material:	
Steel comp e4340 or ste	el comp 8740
Material Specification:	
Mil-s-5000 military speci	fication 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Spe	cification:
Qq-p-416 ty2 cl2 federal	specification single treatment response
Thread Series Designa	tor:
Unc	
Specification Data:	
80205-nas7701 professi	onal/industrial association standard
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	

NSN 5305-01-369-3506

Close Tolerance Screw - Page 2 of 2



Fiig: A003b0

Mil-std (military Standard):

Mil-s-5000 spec.