## NSN 5305-01-369-3508

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-369-3508

3a Thread Direction: Right-hand Thread Length: 0.276 inches 6.276 inches Fastener Length: Between 1.573 inches and 1.603 inches Head Style: Pan Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height: Between 0.087 inches and 0.097 inches
Right-hand Thread Length: 0.276 inches Fastener Length: Between 1.573 inches and 1.603 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Thread Length: 0.276 inches Fastener Length: Between 1.573 inches and 1.603 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
0.276 inches Fastener Length: Between 1.573 inches and 1.603 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Fastener Length:         Between 1.573 inches and 1.603 inches         Head Style:         Pan         Head Diameter:         Between 0.256 inches and 0.270 inches         Head Height:
Between 1.573 inches and 1.603 inches Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Head Style: Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Pan Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Head Diameter: Between 0.256 inches and 0.270 inches Head Height:
Between 0.256 inches and 0.270 inches Head Height:
Head Height:
-
Between 0.087 inches and 0.097 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.1380 inches
Grip Length:
Between 1.302 inches and 1.322 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1131 professional/industrial association standard
Shelf Life:
N/a

## NSN 5305-01-369-3508

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

