NSN 5305-01-369-4804

Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-369-4804

3a Thread Direction: Righ-hand Thread Length: 0.889 inches Fastener Length: Between 0.989 inches and 1.031 inches Head Style: Flat chanfar Head Dimeter: Between 0.431 inches and 0.437 inches Head Height: Between 0.431 inches and 0.437 inches Head Height: Between 0.432 inches and 0.437 inches Head Height: Between 0.432 inches and 0.456 inches Locking Feature: Patch threads or poliet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Ox126 inches and 0.1587 inches Thread Valy Per Inch (tpi): 18 Material: Streed Streed Streed Teatement Specification 1st treatment response or mile-83488, class 3 military specification 2nd treatment response or mile-83488, class 3 military specification 2nd treatment response or mile-83488, class 3 military specification 2nd treatment response or mile-83488, class 3 military specification 2nd treatment response or mile-83488, class 3 military specification 2nd treatment response or mile-83488, class 3 military specification 2nd treatment response or m	Thread Cla	SS:
Right-hand Thread Length: 0.889 inches Fastener Length: Between 0.969 inches and 1.031 inches Head Style: Flat chmfler Head Style: Between 0.431 inches and 0.437 inches Head Height: Between 0.431 inches and 0.437 inches Head Height: Between 0.452 inches and 0.437 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches With Acces Flats: Between 0.1562 inches and 0.1587 inches Thread Diameter: 0.3125 inches With Acces Flats: Between 0.1562 inches and 0.1587 inches Thread Y by Per Inch (tpi): 18 Material: Strate Treatment: Wice Strite: Wich Acces Flats: Between 0.1562 inches and 0.1587 inches <tr< th=""><th></th><th></th></tr<>		
Thread Length: 0.889 inches Fasten Length: Between 0.969 inches and 1.031 inches Hed Style: Flat chamfer Head Style: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pollet threads or strip threads Internal Drive Style: Heard angth: Metandig Mith Access False: Between 0.1562 inches and 0.1587 inches Mith Access False: Between 0.1562 inches and 0.1587 inches Mith Access False: Between 0.1562 inches and 0.1587 inches Thread Quinter or allumium and chromate Store Treatment: Wick-Strift Scals unlikary specification 1st treatment response or mil-e3488, class 3 military specification 2nd treatment response Wick Maccess Wick Maccess Mice Mice Mice Mice Store Treatment: Wick-Strift Scals unlikary specification 1st treatment response or mil-e3488, class 3 military specification 2nd treatment response Mice Mice		action:
0.489 inches Fastener Length: Fastener Length: Between 0.509 inches and 1.031 inches Head Style: Fat chamfer Head Diameter: Between 0.431 inches and 0.437 inches Head Height: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1582 inches and 0.1587 inches Thread Qty Per Inch (tpi): 18 Between 0.1582 inches and 0.1587 inches Stried Stried Stried Stried Freatment: Stried St		
Fastener Length: Between 0.969 inches and 1.031 inches Head Style: Flat chamfer Head Diamoter: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Botween 0.4562 inches and 0.1587 inches Thread Diameter: 0.3125 inches Width Across Flats: Botween 0.4562 inches and 0.1587 inches Thread Oly Per Inch (tpi): 18 Material: Streed Streed Creatment: Zin and chromate or aluminum and chromate Streed Treatment: Zine and chromate or aluminum and chromate Shell Life: Na Shell Life: Na Demilarization: Na Demilarization: Na Demilarization: Na Demilarization:		
Between 0.909 inches and 1.031 inches Had Styie: Flat chamfer Head Diameter: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.437 inches Head Height: Between 0.152 inches and 0.437 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thread Voly Per Inch (tpi): 18 Material: Steel Striege Treatment: Steel Striege Treatment: Steel Striege Treatment Specification 1st treatment response or mile-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shef Life: Na Comments		
Head Siyle: Flat chamfer Flat chamfer Flat chamfer Between 0.431 inches and 0.437 inches Flat chamfer Between 0.152 inches and 0.156 inches Flat chamfer Between 0.152 inches and 0.156 inches Flat chamfer Dicking Feature: Flat chamfer Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Flat chamfer District Stripter Stripter Between 0.1562 inches and 0.1587 inches Flat chamfer District Stripter Stripter Between 0.1562 inches and 0.1587 inches Flat chamfer Distripter Stripter Stripter Between 0.1562 inches and 0.1587 inches Flat chamfer Distripter Stripter Stripter Between 0.1562 inches and 0.1587 inches Flat chamfer Distripter Stripter Stripter Stripter Treatment: Stripter Treatment Distripter Stripter Stripter Treatment specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specificati		
Flat chamfer Head Diameter: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches With Across Flats: Between 0.1562 inches and 0.1587 inches Thready City Per Inch (tpi): 18 Material: Stell Stell <		
Head Diameter: Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thread Qty Per Inch (tpi): 18 Stele Strike Stele Strike Stele Strike Direct Treatment: Inceral Treatment Specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Strike Na Stel Strike Directific Na Strike Strike Strike Strike Mit-cs7115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Strike Na Directific Na Strif Life: Na </td <td></td> <td></td>		
Between 0.431 inches and 0.437 inches Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Strate Treatment: Zinc and chromate or aluminum and chromate Surface Treatment: Unc Sheft Life: Na Sheft Life: Na Dimitidatization: Na Sheft Life: Na S		
Head Height: Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches With Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Strate Treatment: Zuriace Treatment Specification Mil-e-87115, class 1 military specification 1st treatment response or mil-e-83488, class 3 military specification 2nd treatment response Thread Series Designator: Via Dimitifarization: Na Dimitifarization: Na Dimitifarization: Na Shef Life: Na Dimitifarization: Na Dimitifarization: Na Shef Life: Na Dimitifarization: Na Dimitifarization: Na Shef Life: Na <td< td=""><td></td><td></td></td<>		
Between 0.152 inches and 0.156 inches Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Dlameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Oty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shef Life: Unc Unc Shef Life: Unc Cife Cife Cife Cife Cife Cife Cife Cife	Between 0.4	131 inches and 0.437 inches
Locking Feature: Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Stell Strace Treatment Zinc and chromate or aluminum and chromate Strace Treatment Specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment response or mil-c-83488, class 3 military specification 2nd treatment 2nd 2nd 2nd 2nd	Head Heigh	nt:
Patch threads or pellet threads or strip threads Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Material: Steel Stread Freatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Na Chrome		
Internal Drive Style: Hexagon Thread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Surface Treatment: Cinc and chromate or aluminum and chromate Surface Treatment or aluminum and chromate Surface Treatment specification 1 st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: Na Shelf Life: Na SurfaceTreatment: Demilitarization: Na		
Hexagon Thread Diameter: . Dial25 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Sheft Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	Patch threa	ds or pellet threads or strip threads
Tread Diameter: 0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Oty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	nternal Dri	ve Style:
0.3125 inches Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0		
Width Across Flats: Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	Thread Dia	meter:
Between 0.1562 inches and 0.1587 inches Thready Qty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	0.3125 inch	es
Thready Qty Per Inch (tpi): 18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	Width Acro	ss Flats:
18 Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	Between 0.	1562 inches and 0.1587 inches
Material: Steel Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Wil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: V/a Demilitarization: - Demilitarization: No Fiig: A003b0	Thready Qt	y Per Inch (tpi):
Steel Steel Strace Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	18	
Surface Treatment: Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:	
Zinc and chromate or aluminum and chromate Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Steel	
Surface Treatment Specification: Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: A003b0	Surface Tre	eatment:
Mil-c-87115, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Zinc and ch	romate or aluminum and chromate
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Surface Tre	eatment Specification:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Mil-c-87115	, class 1 military specification 1st treatment response or mil-c-83488, class 3 military specification 2nd treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Thread Ser	ies Designator:
N/a Unit Of Measure: Demilitarization: No Fiig: A003b0	Jnc	
Unit Of Measure: Demilitarization: No Fiig: A003b0	Shelf Life:	
 Demilitarization: No Fiig: A003b0	N/a	
Demilitarization: No Fiig: A003b0	Unit Of Mea	asure:
No Fiig: A003b0	-	
Fiig: A003b0	Demilitariz	ation:
A003b0	No	
	Fiig:	
Mil-std (military Standard):	4003b0	
	Mil-std (mil	itary Standard):