Socket Head Cap Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-369-4805

Thread Class:
2a
Za Thread Direction:
Right-hand
Thread Length:
Between 1.500 inches and 2.190 inches
Fastener Length:
Between 2.190 inches and 2.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Hole Diameter:
Between 0.061 inches and 0.067 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
Between 0.375 inches and 0.379 inches
Hole Quantity:
7
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches threads32.0 microinches fastener
Material:
Steel
Surface Treatment:
Cadmium and chromate

NSN 5305-01-369-4805

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0