

View Online at <https://aerobasegroup.com/nsn/5305-01-369-5511>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.203 inches

**Fastener Length:**

Between 0.587 inches and 0.607 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.317 inches

**Internal Drive Style:**

Cross recess type 1

**Material Accommodated Thickness:**

Between 0.075 inches and 0.089 inches

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Iron alloy 660 locking featuresteel comp 304 stand-off

**Material Specification:**

Ams5737 assn standard single material response locking featuremil-s-23195 military specification single material response stand-off

**Surface Treatment:**

Passivate locking featurepassivate stand-off

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response locking featureqq-p-35 federal specification single treatment response stand-off

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-23195 spec.